



Red Hat System Administration II (RH134-RHEL8)

Installation and Configuration Guide

Document Version: 2019-11-15

Copyright © 2019 Network Development Group, Inc.
www.netdevgroup.com

NETLAB Academy Edition, NETLAB Professional Edition, and NETLAB+ are registered trademarks of Network Development Group, Inc.

VMware is a registered trademark of VMware, Inc.

"Red Hat," Red Hat Linux, and the Red Hat "Shadowman" logo are trademarks or registered trademarks of Red Hat, Inc. in the US and other countries.

Contents

1	Introduction	3
1.1	Introducing the Red Hat System Administration II (RH134-RHEL8) Pod	3
2	Planning.....	4
2.1	Pod Creation Workflow.....	4
2.2	Pod Resource Requirements.....	5
2.3	ESXi Host Server Requirements.....	5
2.4	NETLAB+ Requirements	5
2.5	NETLAB+ Virtual Machine Infrastructure Setup.....	6
2.6	Software Requirements	6
2.7	Networking Requirements	6
3	Obtaining Software and Licenses.....	7
3.1	Downloading OVF Files.....	7
4	Master Pod Configuration.....	8
4.1	Deploying Virtual Machine OVF/OVA Files	8
4.2	Modify Virtual Machines.....	9
4.2.1	VM Credentials.....	10
4.3	NETLAB+ Virtual Machine Inventory Setup.....	10
4.4	Building the Master Red Hat System Administration II (RH134-RHEL8) Pod.....	11
4.4.1	Enabling the Labs in Course Manager	11
4.4.2	Create the Master Pod.....	11
4.4.3	Attach Virtual Machines to the Master Pod	13
4.4.4	Create Snapshots for the Master Virtual Machines	13
4.4.5	Set the Revert to Snapshot	16
5	Pod Cloning	17
5.1	Linked Clones and Full Clones	17
5.2	Creating User Pods	17
5.3	Cloning Your Master Pod to a Second Host	19
5.4	Creating User Pods on the Second Host	21
5.5	Assigning Pods to Students, Teams, or Classes.....	21

1 Introduction

This document provides detailed guidance on performing the installation and configuration of the *Red Hat System Administration II (RH134-RHEL8)* pod on the *NETLAB+ VE* system.

1.1 Introducing the Red Hat System Administration II (RH134-RHEL8) Pod

The *Red Hat System Administration II (RH134-RHEL8)* pod is a 100% virtual machine pod consisting of 1 virtual machine. Linked together through virtual networking, the 1 virtual machine provides the environment for a student or a team to perform the *Red Hat System Administration II (RH134-RHEL8)* labs.



2 Planning

This guide provides specific information pertinent to delivering the *Red Hat System Administration II (RH134-RHEL8)* pod. The [*NETLAB+ Remote PC Guide Series*](#) provides the prerequisite guidance for setting up your *VMware* infrastructure, including:

- An introduction to virtualization using *NETLAB+*.
- Detailed setup instructions for standing up *VMware vCenter* and *VMware ESXi*.
- Virtual machine and virtual pod management concepts using *NETLAB+*.

This document assumes that you have set up virtual machine infrastructure in accordance with the [*NETLAB+ Remote PC Guide Series*](#). The planning information below refers to specific sections in the *Remote PC Guide* when applicable.

2.1 Pod Creation Workflow

The following list is an overview of the pod setup process.

1. Obtain the master virtual machine images required for the master pod.
2. Deploy the master virtual machine images to your *VMware vCenter Appliance*.
 - a. Deploy virtual machines using **Thin Provisioning** to reduce storage consumption.
 - b. Make necessary adjustments to each virtual machine in the environment.
 - i. Insert/Verify manual **MAC** addresses.
 - ii. Change the default network to **SAFETY NET**.
 - iii. Any other configuration changes mentioned in this guide.
3. Import the deployed virtual machines to the *NETLAB+ Virtual Machine Inventory*.
4. Activate or license the required software on each virtual machine when prompted.
5. Take a snapshot of each virtual machine in the master pod labeled **GOLDEN_MASTER** after all configurations and licensing have taken effect. The **GOLDEN_MASTER** snapshot is used to clone virtual machine images for the user pods.
6. Use the *NETLAB+ Pod Cloning* feature to create student pods from the master pod.
7. If multiple hosts are used in the *NETLAB+* environment, make a **Full Clone** of the master pod on the initial host (Host A) to the subsequent host (Host B) and so on using the *NETLAB+ Pod Cloning* feature.

2.2 Pod Resource Requirements

The *Red Hat System Administration II (RH134-RHEL8)* course will consume 22.6 GB of storage per each master pod instance.

The following table provides details of the storage requirements for each of the virtual machines in the pod.

Virtual Machine	OVF/OVA	Initial Master Pod (Thin Provisioning)
Foundation0	18.9	22.6
Total	18.9 GB	22.6 GB

2.3 ESXi Host Server Requirements

Please refer to the *NDG* website for specific *ESXi* host requirements to support virtual machine delivery: <http://www.netdevgroup.com/content/vmita/requirements/>

The deployment of the *RH134* VM from the *Red Hat System Administration II (RH134-RHEL8)* pod requires a *VMware vSphere Version of 6.0* or greater for the infrastructure due to the *Hardware Version* of select *RH134* VM (*version 11*) in the pod.

Please Note

The number of **active** pods that can be used simultaneously depends on the *NETLAB+* product edition, appliance version and the number of *VMware ESXi* host servers meeting the hardware requirements specifications.

For current *ESXi* server requirements and active pod count, refer to the following URL:

http://www.netdevgroup.com/support/remote_pc.html#vm_host_server_specifications.

2.4 NETLAB+ Requirements

Installation of *Red Hat System Administration II (RH134-RHEL8)* pods, as described in this guide, requires that you are running *NETLAB+ VE*.

Previous versions of *NETLAB+* do not support requirements for the *Red Hat System Administration II (RH134-RHEL8)* course on the physical host servers.

Please refer to the [*NETLAB+ Remote PC Guide Series*](#).

2.5 NETLAB+ Virtual Machine Infrastructure Setup

The *NETLAB+ Virtual Machine Infrastructure* setup is described in the following sections of the [*NETLAB+ Remote PC Guide Series*](#):

- *Registering a Virtual Datacenter in NETLAB+*
- *Adding ESXi hosts in NETLAB+*
- *Proactive Resource Awareness*



It is important to configure *Proactive Resource Awareness* to maximize the number of active pods per physical *ESXi* host.

2.6 Software Requirements

For the purpose of software licensing, each virtual machine is treated as an individual machine, PC, or server. Please refer to the specific vendor license agreements (and educational discount programs, if applicable) to determine licensing requirements for your virtual machines' software, operating system, and applications.

The minimum virtual infrastructure software required for standing up this pod is in the following table.

Virtual Infrastructure Requirements	
Software	Version
vSphere ESXi	6.0
vCenter Server	6.0

2.7 Networking Requirements

To accommodate the movement of large *VMs*, *OVF/OVAs*, and *ISO* disk images from one host to another, gigabit Ethernet or better connectivity is recommended to interconnect your *NETLAB+*, *vCenter Server* system and *ESXi* host systems.

The two standard networking models recommended to interconnect your servers are described in detail in the *Networking Models* section of the [*Remote PC Guide Series, Volume 1 - Introduction and Planning*](#).

3 Obtaining Software and Licenses

3.1 Downloading OVF Files

The virtual machines are made available as *Open Virtualization Format (OVF)* or *Open Virtualization Archive (OVA)* files. These files are available for download from *CSSIA*.

To request access to the preconfigured virtual machine templates from *CSSIA*:

1. Go to the *CSSIA Resources* page: <https://www.cssia.org/cssiaresources/>
2. Select **CSSIA VM Image Sharing Agreement**.
3. Complete and submit your access request by following the instructions on the request form.
4. *CSSIA* will provide, via email, password-protected download links. Access to the download links is provided only to customers who are current with their NETLAB+ support contract and are participants in the appropriate partner programs (*i.e.*, Cisco Networking Academy, VMware IT Academy, Red Hat Academy, and/or Palo Alto Networks).
5. Once all virtual machines have been downloaded, they can be deployed following the steps in the appropriate pod installation guide. Each virtual machine is deployed individually.

4 Master Pod Configuration

4.1 Deploying Virtual Machine OVF/OVA Files

Deploy the *OVF/OVA* files you have downloaded to your host server.

1. Navigate to your **vSphere Client** using your management workstation, ensure that your downloaded *OVA/OVF* files are accessible on this machine, and then connect to your **vCenter Server**.
2. From the *vSphere Client* interface, navigate to **Hosts and Clusters**.
3. Right-click on the target **ESXi Host Server** and select **Deploy OVF Template**.
4. In the *Deploy OVF Template* window, on the *Select source* step, select the **Local File** radio button and click **Browse**.
5. Locate and select one of the VMs for the pod, click **Open**.

Please Note

Only one VM can be selected using this wizard. The process will have to be repeated for the remaining VMs.

6. Verify that the VM file path and name appear next to the *Browse* button and click **Next**.
7. In the *Review details* section, make sure to fill the checkbox for **Accept extra configuration options (if present)** and click **Next**.
8. In the *Select name and folder* section, change the name of the virtual machine to something that is easy to manage. You can use the names provided in the list below as names for the virtual machines if you do not have a set naming convention. Select the appropriate datastore and click **Next**.

Virtual Machine Topology Name	Virtual Machine Deployment Name
Foundation0	RH134_RHEL8_Master.Foundation0

9. On the *Select Storage* step, choose the appropriate storage device and make sure that **Thin Provision** is selected. Click **Next**.
10. In the *Setup networks* section, select **SAFETY NET** as the destination and click **Next**.



If **SAFETY NET** is not available, refer to the *Create a Safe Staging Network* section in the [Remote PC Guide Series – Volume 2](#).

11. In the *Ready to complete* section, make sure **Power on after deployment** is **unchecked** and confirm the settings. Click **Finish**.
12. *vCenter* will begin deploying the virtual machine. This may take some time depending on the speed of your connection, HDDs, etc.

4.2 Modify Virtual Machines

Once the virtual machines are imported onto the host, verify the configurations. The following steps will guide you through the process.

1. In the *vSphere Client* interface, right-click on the imported virtual machine and select **Edit Settings**.
2. For all of the virtual machines, manually assign the *MAC* addresses for each *NIC*. The table below identifies the *MAC* addresses per *NIC*.

Virtual Machine	NIC	MAC
Foundation0	1	00:50:56:99:d4:1a

Edit Settings | RH134_RHEL8_Master.Foundation0 X

[Virtual Hardware](#) [VM Options](#) [ADD NEW DEVICE](#)

> CPU	4	i
> Memory	8	GB
> Hard disk 1	120	GB
<input checked="" type="checkbox"/> Network adapter 1	SAFETY NET	
Status	<input checked="" type="checkbox"/> Connect At Power On	
Adapter Type	VMXNET 3	
DirectPath I/O	<input checked="" type="checkbox"/> Enable	
MAC Address	00:50:56:99:d4:1a	Manual
> CD/DVD drive 1	Client Device	
> Video card	Specify custom settings	
VMCI device	Device on the virtual machine PCI bus that provides support for the virtual machine communication interface	
SATA controller 0	AHCI	
> Other	Additional Hardware	

[CANCEL](#) [OK](#)

4.2.1 VM Credentials

For your reference, the following table provides a list of the credentials for the systems in the pod:

Machine	User name	Password
Foundation0	kiosk	redhat

4.3 NETLAB+ Virtual Machine Inventory Setup

This section will guide you in adding your templates to the *Virtual Machine Inventory* of your **NETLAB+** system.

1. Log in to your **NETLAB+ VE** system using the *administrator* account.
2. Click on the **Virtual Machine Infrastructure** icon.



3. Click the **Virtual Machine Inventory** icon.



Virtual Machine Inventory

Import, clone, and manage the inventory of virtual machines to be used with NETLAB+.

4. Click the **Import Virtual Machines** button located at the bottom of the list.



5. Select the appropriate datacenter from the list where your master VMs reside.
6. Select the checkbox next to the virtual machine you had just deployed and click **Import Selected Virtual Machines**.



7. When the *Configure VMs* page loads, you can set your virtual machine parameters.

- a. Check the drop-down box for the correct operating system for each imported virtual machine.

- b. Change **Role** to **Master** for each VM.
- c. Add any comments for each virtual machine in the last column.



It is advised to leave the *Version* and *Build* numbers for reference when requesting *NDG* support.

- d. Verify your settings and click **Import (X) Virtual Machines** (notice the number in parenthesis is dynamic, depending on the amount of VMs selected).

 **Import (1) Virtual Machines**

- e. Verify all *Import Statuses* report back with **OK** and then click on the **Dismiss** button.
- f. Verify that your virtual machines show up in the inventory.

For additional information, please refer to the [NETLAB+ VE Administrator Guide](#).

4.4 Building the Master Red Hat System Administration II (RH134-RHEL8) Pod

This section will assist you in adding the *Red Hat System Administration II (RH134-RHEL8)* pod to your *NETLAB+* system.

4.4.1 Enabling the Labs in Course Manager

Please refer to the *Course Manager* section of the [NETLAB+ VE Administrator Guide](#) on how to enable content. Please install the **Red Hat Academy System Administration II (RH134) - v8.0** course.

4.4.2 Create the Master Pod

This section will assist you in adding the *Red Hat System Administration II (RH134-RHEL8)* pod to your *NETLAB+* system.

1. Log into **NETLAB+ VE** with the *administrator* account.
2. Click on the **Pods** icon.



3. Create a new pod by scrolling to the bottom and clicking the **Create New Pod** button.

 **Create New Pod**

4. On the *New Pod Wizard*, page click **Next**.
5. Then, click on the **Red Hat SysAdmin II – RH134** pod entry from the list of installed pod types.



6. On the *New Pod* window, input a value into the **Pod ID** and **Pod Name** fields. Click **Next**.

 New Pod								
Pod Type  Red Hat SysAdmin II	Pod ID <input style="border: 2px solid red; width: 100%; height: 25px; margin-bottom: 5px;" type="text" value="1000"/> Pod Name <input style="border: 2px solid red; width: 100%; height: 25px;" type="text" value="RH134_RHEL8_H120_M1000"/>							
<input style="border: 2px solid red; padding: 5px; margin-right: 10px;" type="button" value="Next"/> <input style="border: 1px solid #ccc; padding: 5px;" type="button" value="Help"/>								
Used Pod IDs <table border="1" style="margin-left: auto; margin-right: 0; border-collapse: collapse;"> <tr><td>1</td></tr> <tr><td>5</td></tr> <tr><td>10</td></tr> <tr><td>15</td></tr> <tr><td>20</td></tr> <tr><td>25</td></tr> <tr><td>105</td></tr> </table>		1	5	10	15	20	25	105
1								
5								
10								
15								
20								
25								
105								



The **Pod ID** determines the order in which the pods will appear in the scheduler. It is best practice to use a block of sequential ID numbers for the *Pod Id* that allows for the number of pods you are going to install.

The **Pod Name** identifies the pod and is unique per pod. Here we used the name of the lab set or course in a shortened form along with a host identifier (H120), the type and number of the pod (M1000).

7. To finalize the wizard, click **OK**.

For additional information, please refer to the [NETLAB+ VE Administrator Guide](#).

4.4.3 Attach Virtual Machines to the Master Pod

Update the master pod to associate the virtual machines with the newly created pod.

1. Click on the **Red Hat System Administration II (RH134-RHEL8)** master pod from the pod list.

1000	Red Hat SysAdmin II	RH134_RHEL8_H120_M1000
------	------------------------	------------------------

2. Click on the **Action** dropdown next to the virtual machine you are about to assign and select **Attach VM**.

The screenshot shows a table of PC inventory. A red box highlights the 'Action' dropdown menu for the first row, which contains the text 'Foundation 0' and status 'ABSENT'. The dropdown menu includes options: 'View', 'Settings', 'Attach VM' (which is highlighted with a red box), 'Remove VM From...', and 'Snapshots'.

3. Select the corresponding virtual machine from the inventory list.

Virtual Machine Name	Operating System	Role
RH134_RHEL8_Master.Foundation0	Linux	Master

4. Click **OK** to confirm the VM attachment

4.4.4 Create Snapshots for the Master Virtual Machines

In order to proceed with pod cloning, snapshots must be created on each of the pod's virtual machines.



Verify that all VMs are still powered off before taking snapshots.

1. Make sure to view the **Red Hat System Administration II (RH134-RHEL8)** master pod you just assigned machines to. In the pod view, click on the drop-down

menu option underneath the *Action* column for a specific VM and select **Snapshots**.

The screenshot shows a table titled "Remote PC 1" with one item. The columns are: PC Name, VM, Operating System, VM Role, Runtime Host, and Action. The "Action" column for the single entry has a dropdown arrow icon. Below the table are several buttons: Dismiss, Pod Settings, Clone Pod, View Reservations, Configure Pod ACL, and a "S" icon. To the right of these buttons is a vertical "Action" menu with options: View, Settings, Attach VM, Remove VM From..., and Snapshots. The "S" icon and the "Snapshots" menu item are both highlighted with red boxes.


2. In the *Snapshot Manager* window, click on **Take**. This will take a snapshot of the current state of the virtual machine.

The screenshot shows the "Snapshot Manager" window. On the left, there is a tree view showing a folder named "RH134_RHEL8_Master.Foundation0" with a sub-node "You Are Here!". On the right, there are fields for "Name:" and "Description:". Below the tree view are buttons: "Take" (highlighted with a red box), "Delete All", "Go To", "Edit", and "Delete". At the bottom is a "Dismiss" button.




Any changes made after this will require a new snapshot or those changes will not reflect in the reset state of the pod or its clones.

3. In the *Take Snapshot* window, type **GOLDEN_MASTER** into the *Name* text field, or you may choose another naming convention as long as it is consistent for easy management. Click **OK**.



It is recommended to use *GOLDEN_MASTER* as the snapshot name when working with normalized pod types.

4. In the *Snapshot Manager* window, notice the snapshot is created. Click the **Dismiss** button.



At this point it is good to verify that you have only one snapshot on the virtual machine. Multiple snapshots increase the likelihood of having problems, especially if the snapshots are named the same. Also, the more snapshots a virtual machine has, the slower the performance and the more drive space is used.

4.4.5 Set the Revert to Snapshot

1. Make sure to view the **Red Hat System Administration II (RH134-RHEL8)** master pod you just created snapshots for. In the pod view, click on the drop-down menu option underneath the *Action* column and select **Settings**.

The screenshot shows a table of pods. The first row is for 'Remote PC 1'. The 'Action' column for the first pod has a dropdown menu open, with the 'Settings' option highlighted by a red box.

PC Name	VM	Operating System	VM Role	Runtime Host	Action
Foundation 0	RH134_RHEL8_Master.Foundation0	Linux	MASTER	172.30.10.58	<input checked="" type="checkbox"/>

Buttons at the bottom of the pod view include: Dismiss, Pod Settings (highlighted), Clone Pod, View Reservations, Configure Pod ACL, View, Settings (highlighted), Attach VM, Remove VM From..., and Snapshots.

2. In the virtual machine's *Settings* window, click on the *Revert to Snapshot* drop-down and select **GOLDEN_MASTER** and then click the **Submit** button.



This sets the snapshot on the virtual machine that will get reverted to each time the pod is scheduled.

The screenshot shows the 'Foundation 0 Settings' dialog box. It contains the following fields:

- PC Name: Foundation 0
- PC Type: Virtual Machine
- Datacenter: ContDev01
- Virtual Machine: RH134_RHEL8_Master.Foundation0
- Role: Master
- Revert to Snapshot: GOLDEN_MASTER (highlighted with a red box)
- Shutdown Preference: Graceful Shutdown
- Guest Operating System: Linux
- Options (checkboxes):
 - enable remote display auto-configuration
 - enable network auto-configuration
 - enable advanced setting auto-configuration
 - enable minimum requirements verification

At the bottom are three buttons: Submit (highlighted with a red box), Cancel, and Help.

3. Click **OK** to confirm.

5 Pod Cloning

This section will help you create multiple student pods. The following sections describe the *NETLAB+* pod cloning feature used to create student pods on one or two host systems.

5.1 Linked Clones and Full Clones

NETLAB+ can create *linked clones* or *full clones*.

A **linked clone** (or linked virtual machine) is a virtual machine that shares virtual disks with the parent (or master) virtual machine in an ongoing manner. This conserves disk space and allows multiple virtual machines to use the same software installation. Linked clones can be created very quickly because most of the disk is shared with the parent VM.

A **full clone** is an independent copy of a virtual machine that shares nothing with the parent virtual machine after the cloning operation. Ongoing operation of a full clone is entirely separate from the parent virtual machine.

5.2 Creating User Pods

The following section describes how to create user pods on the same *VMware Host* system that holds your master pod's virtual machines. In this scenario, we will create linked virtual machines using the *NETLAB+* pod cloning utility.



Make sure the pod status is **Offline** prior to continuing. The cloning process requires the pod be offline. Since this is a master pod, which is used for cloning other pods, we will keep it offline to create the instructor and student pods from.


1. Login into **NETLAB+ VE** with the *administrator* account.
2. Select the **Pods** icon.



Pods

3. Click on the master pod.
4. Make sure the pod is offline by selecting **Take Pod Offline**.

- Click the **Clone Pod** button to create a new pod-based on the settings and snapshots of this pod.



- Input a new ID value into the **New Pod ID** field. It is advised to keep the pods in numerical order. If the *pod IDs* are not in numerical order, they will not show up in the scheduler in numerical order. Click **Next**.
- Enter a name for the cloned pod into the **New Pod Name** text field. For example, **RH134_RHEL8_H120_S1001**. Click **Next**.



The **Pod Name** identifies the pod and is unique per pod. Here we used the name of the lab set or course in a shortened form along with a host identifier (H120), the type and number of the pod (S1001).

- When the action has finished processing, you are presented with a *Clone Pod* configuration wizard. Verify the following:

Source Virtual Machine:

- From Snapshot* should be set to the **GOLDEN_MASTER** snapshot you created previously.

Target Virtual Machine:


- For *Type*, verify that **Linked** is selected.
- For *Role*, verify that the **Normal** role is selected.
- For *Take Snapshot*, verify that **GOLDEN_MASTER** is input.

Source Virtual Machine		→	Target Virtual Machine	
VM Name	RH134_RHEL8_Master.Foundati...		VM Name	RH134_RHEL8_H120_S1001.Foundati...
From Snapshot	GOLDEN_MASTER		Type	Linked
			Role	Normal
			Runtime Host	[dropdown]
			Datastore	[dropdown]
			Storage	On Demand
			Take Snapshot	GOLDEN_MASTER

- When you are done changing settings, click **Clone Pod**. This should complete within a minute as we are creating linked virtual machines.

Clone Pod

- When the pod clone process is finished, click **OK**.
- If you want to dedicate this pod to a particular class, team, or student, use the *Pod ACLs* feature. For details, see the [*NETLAB+ VE Instructor Guide*](#).
- Click the **Online** button on the *Pod Management* page to activate the pod.



The user pod can now be reserved. When the reservation becomes active, *NETLAB+* will automatically configure virtual machines and virtual networking for the active reservation.



The *GOLDEN_MASTER* snapshot is the starting point for all pods. We recommend that you reserve the 1st pod and conduct some labs to make sure the snapshot images work correctly. If there are defects, make corrections to the images to the master pod and retake the *GOLDEN_MASTER* snapshot before creating additional pods.


5.3 Cloning Your Master Pod to a Second Host

For this task, we will use the pod cloning utility to copy our master pod to a second host.

- Login into **NETLAB+ VE** with the *administrator* account.
- Click on the **Pods** icon.



- Click on the master pod.
- Make sure the pod is offline by selecting **Take Pod Offline**.
- Click the **Clone** button to create a new pod-based on the settings of this pod.



6. Input a new ID value into the **New Pod ID** field. It is advised to keep the pods in numerical order. If the pod IDs are not in numerical order, they will not show up in the scheduler in numerical order. Click **Next**.
7. Enter a name for the cloned pod into the **New Pod Name** field. For example, **RH134_RHEL8_H130_M1000**. Click **Next**.



The **Pod Name** identifies the pod and is unique per pod. Here we used the name of the lab set or course in a shortened form along with a host identifier (H130), the type and number of the pod (M1000).

8. When the action has finished processing, you are presented with a *Clone Pod* configuration wizard. Notice each VM has its own tab. Go through each tab and verify the following:

Source Virtual Machine:

- a. *From Snapshot* should be set to the **GOLDEN_MASTER** snapshot you created previously.

Target Virtual Machine:

- a. For *Type*, verify that **Full** is selected.
- b. For *Role*, verify that the **Master** role is selected.
- c. For *Take Snapshot*, verify that **GOLDEN_MASTER** is input.
- d. For *Runtime Host*, select the second host system (which should be different than the system you are cloning from).

Foundation 0		→	Target Virtual Machine	
Source Virtual Machine			Target Virtual Machine	
VM Name	RH134_RHEL8_Master.Foundation 0	VM Name	RH134_RHEL8_H130_M1000.Foundation 0	
From Snapshot	GOLDEN_MASTER	Type	Full	
		Role	Master	
		Runtime Host		
		Datastore		
		Storage	On Demand	
		Take Snapshot	GOLDEN_MASTER	

9. When you are done changing settings, click **Clone Pod**. This may take up to 30 minutes as full copies are being made. You may navigate away from the cloning progress screen, and then later return to the pod to check progress.

10. When the pod clone process is finished, click **OK**.

5.4 Creating User Pods on the Second Host

To create user pods on the second host, repeat the steps to create user pods on the first host (see *Creating User Pods*), substituting the second master pod (created in the previous section) as the cloning source.

5.5 Assigning Pods to Students, Teams, or Classes

Please refer to the [*NETLAB+ VE Instructor Guide*](#) for details on using the *Pod ACLs* feature.